

Contractors **Win** with Lutron Sensors™

Qualifying Sensors

Maestro® In-Wall and Radio Powr Savr™ occupancy/vacancy sensors

Model Number	Description	Model Number	Description
MS-Z101-*	0-10V dimmer with PIR sensor; occupancy/vacancy; multi-location/3-way/single pole; 120-277V – NEW!	UMS-OPS6-DDV-	6A per circuit, 120-277V PIR dual-circuit occupancy/vacancy; 4.4A fan (120V only) per circuit; BAA compliant
MS-Z101-V*	0-10V dimmer with PIR sensor; vacancy-only; multi-location/3-way/single pole 120-277V – NEW!	MS-OPS6-DDV-	6A per circuit, 120-277V PIR dual-circuit occupancy/vacancy; 4.4A fan (120V only) per circuit
MS-A102-	6A, 120-277V dual-tech occupancy/vacancy sensor, 4.4A fan (120V only); no neutral – NEW!	MS-PPS6-DDV-	6A per circuit, 120-277V PIR dual-circuit partial-on occupancy/ vacancy, 4.4A fan (120V only) per circuit
MS-A102-V-	6A, 120-277V dual-tech vacancy-only; 4.4A fan (120V only); no neutral – NEW!	MSCL-OP153M-	C·L® dimmer with PIR sensor; occupancy/vacancy; single-pole/3-way/multi-location; 150W CFL/LED, 600W inc/hal
MS-A202-	6A per circuit, 120-277V dual-tech dual-circuit occupancy/vacancy, 4.4A fan (120V only) per circuit; no neutral – NEW!	MSCL-VP153M-	C·L dimmer with PIR sensor; vacancy-only; single-pole/3-way/multi-location; 150W CFL/LED, 600W inc/hal
MS-B102-	6A, 120-277V dual-tech occupancy/vacancy sensor, 4.4A fan (120V only); neutral required	LRF2-OCR2B-P-	wireless ceiling-mount occupancy/vacancy sensor
MS-B102-V-	6A, 120-277V dual-tech vacancy only; 4.4A fan (120V only); neutral required	LRF2-OHLB-P-	wireless hallway occupancy/vacancy sensor
MS-B202-	6A per circuit, 120-277V dual-tech dual-circuit occupancy/vacancy, 4.4A fan (120V only) per circuit; neutral required	LRF2-OKLB-P-	wireless corner-mount occupancy/vacancy sensor
MS-OPS2-	2A lighting, 120V PIR occupancy/vacancy; single pole	LRF2-OWLB-P-	wireless wall-mount occupancy/vacancy sensor
MS-VPS2-	2A lighting, 120V PIR vacancy only; single pole	LRF2-VCR2B-P-	wireless ceiling-mount vacancy-only sensor
MS-OPS5M-	5A lighting, 120V PIR occupancy/vacancy; 3A fan, multi-location/3-way/single pole	LRF2-VHLB-P-	wireless hallway vacancy-only sensor
MS-VPS5M-	5A lighting, 120V PIR vacancy only; 3A fan, multi-location/3-way/single pole	LRF2-VKLB-P-	wireless corner-mount vacancy-only sensor
MS-OPS6M2-DV-	6A, 120-277V PIR occupancy/vacancy, 3A fan (120V only); no neutral	LRF2-VWLB-P-	wireless wall-mount vacancy-only sensor
MS-VPS6M2-DV-	6A, 120-277V PIR vacancy only, 3A fan (120V only); no neutral	ULRF2-OCR2B-P-	wireless ceiling-mount occupancy/vacancy sensor; BAA compliant
MS-OPS6M2N-DV-	6A, 120-277V PIR occupancy/vacancy, 3A fan (120V only); neutral required	ULRF2-OHLB-P-	wireless hallway occupancy/vacancy sensor; BAA compliant
MS-VPS6M2N-DV-	6A, 120-277V PIR vacancy only, 3A fan (120V only); neutral required	ULRF2-OKLB-P-	wireless corner-mount occupancy/vacancy sensor; BAA compliant
MS-OPS6M2U-DV-	6A, 120-277V PIR occupancy/vacancy, 3A fan (120V only); configurable ground or neutral wire	ULRF2-OWLB-P-	wireless wall-mount occupancy/vacancy sensor; BAA compliant
MS-VPS6M2U-DV-	6A, 120-277V PIR vacancy only, 3A fan (120V only)	ULRF2-VCR2B-P-	wireless ceiling-mount vacancy-only sensor; BAA compliant
UMS-OPS6M-DV	6A, 120-277V PIR occupancy/vacancy, 3A fan (120V only); no neutral; BAA compliant	ULRF2-VHLB-P-	wireless hallway vacancy-only sensor; BAA compliant
UMS-OPS6M2-DV	6A, 120-277V PIR occupancy/vacancy, 3A fan (120V only); no neutral; BAA compliant	ULRF2-VKLB-P-	wireless corner-mount vacancy-only sensor; BAA compliant
		ULRF2-VWLB-P-	wireless wall-mount vacancy-only sensor; BAA compliant

* Can order now; available to ship November 2014

 **NEW!**

© 08/2014 Lutron Electronics Co., Inc. | P/N 368-3705 REV A

